

Description

Fastener Length: 2-1/32", Thread: 5/8-18, Thread Length: 29/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6710DU30
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-578-5423
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS6710DU30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.892 Inches Minimum And 0.912 Inches Maximum
Fastener Length:	2.012 Inches Minimum And 2.042 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.312 Inches Minimum And 0.327 Inches Maximum
Width Between Flats:	0.920 Inches Minimum And 0.940 Inches Maximum
Grip Diameter:	0.623 Inches Minimum And 0.624 Inches Maximum
Nominal Thread Diameter:	0.625 Inches
Grip Length:	1.875 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6710DU30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.