

Description

Fastener Length: 3/4", Thread: 23/64-16, Thread Length: 51/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6712D27
Minimum Qty (MOQ):	1
NSN:	5306-01-552-5340
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6712D27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.799 Inches Nominal
Fastener Length:	0.750 Inches Nominal
Head Style:	Hexagon
Head Height:	0.375 Inches Minimum And 0.390 Inches Maximum
Width Between Flats:	0.500 Inches Nominal
Grip Diameter:	0.748 Inches Minimum And 0.749 Inches Maximum
End Item Identification:	Fa-18e, Fa18f
Nominal Thread Diameter:	0.366 Inches
Grip Length:	1.688 Inches Nominal
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Special Features:	Drilled Shank, Hole Diameter 0.141
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5753 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6712D27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.