



Military-Fasteners.com

P/N NAS6712D27

Description

Fastener Length: 3/4", Thread: 23/64-16, Thread Length: 51/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6712D27 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-01-552-5340 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6712D27 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.799 Inches Nominal |
| Fastener Length: | 0.750 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.375 Inches Minimum And 0.390 Inches Maximum |
| Width Between Flats: | 0.500 Inches Nominal |
| Grip Diameter: | 0.748 Inches Minimum And 0.749 Inches Maximum |
| End Item Identification: | Fa-18e, Fa18f |
| Nominal Thread Diameter: | 0.366 Inches |
| Grip Length: | 1.688 Inches Nominal |
| Thread Quantity Per Inch: | 16 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Special Features: | Drilled Shank, Hole Diameter 0.141 |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5753 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6712D27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.