

Description

Fastener Length: 2-15/32", Thread: 3/4-16, Thread Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6712DU23
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-525-8874
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS6712DU23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.016 Inches Minimum And 1.066 Inches Maximum
Fastener Length:	2.479 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.375 Inches Minimum And 0.390 Inches Maximum
Width Between Flats:	1.052 Inches Minimum And 1.064 Inches Maximum
Grip Diameter:	0.7485 Inches Minimum And 0.7490 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole
End Item Identification:	Rq-4a
Nominal Thread Diameter:	0.750 Inches
Grip Length:	1.438 Inches Nominal
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.639 Inches Minimum First Hole And 2.689 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Bolt,hex Head,close Tolerance,a286 Cres,long Threads,nonlocking
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6712DU23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.