

P/N NAS6712DU25

Description

Fastener Length: 2-39/64", Thread: 3/4-16, Thread Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6712DU25

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-457-1397

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc



^{*} See page 2 for technical characteristics

P/N NAS6712DU25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.016 Inches Minimum And 1.066 Inches Maximum
Fastener Length:	2.588 Inches Minimum And 2.618 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.375 Inches Minimum And 0.390 Inches Maximum
Width Between Flats:	1.052 Inches Minimum And 1.064 Inches Maximum
Grip Diameter:	0.7485 Inches Minimum And 0.7490 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole
Nominal Thread Diameter:	0.750 Inches
Grip Length:	1.552 Inches Minimum And 1.572 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.639 Inches Minimum First Hole And 2.689 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6712DU25 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.