

Description

Length: 3-3/64", Thread: 3/4-16, Thread Length: 1-1/16", NAS6712 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6712U32
Minimum Qty (MOQ):	1
NSN:	5306-01-361-7924
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6712U32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.016 Inches Minimum And 1.066 Inches Maximum
Fastener Length:	3.026 Inches Minimum And 3.056 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.375 Inches Minimum And 0.390 Inches Maximum
Width Between Flats:	1.052 Inches Minimum And 1.065 Inches Maximum
Grip Diameter:	0.7485 Inches Minimum And 0.7490 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams7531 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6712U32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.