

**Description**

Length: 3-3/64", Thread: 3/4-16, Thread Length: 1-1/16", NAS6712 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6712U32
Minimum Qty (MOQ):	1
NSN:	5306-01-361-7924
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS6712U32 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.016 Inches Minimum And 1.066 Inches Maximum
<b>Fastener Length:</b>	3.026 Inches Minimum And 3.056 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.375 Inches Minimum And 0.390 Inches Maximum
<b>Width Between Flats:</b>	1.052 Inches Minimum And 1.065 Inches Maximum
<b>Grip Diameter:</b>	0.7485 Inches Minimum And 0.7490 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Grip Length:</b>	1.990 Inches Minimum And 2.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams7531 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6712U32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.