



Military-Fasteners.com

P/N NAS6714DU27

Description

Fastener Length: 2-7/8", Thread: 7/8-14, Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6714DU27
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-457-1838
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N NAS6714DU27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.184 Inches Nominal
Fastener Length:	2.857 Inches Minimum And 2.887 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.438 Inches Minimum And 0.453 Inches Maximum
Width Between Flats:	1.239 Inches Minimum And 1.252 Inches Maximum
Grip Diameter:	0.8730 Inches Minimum And 0.8740 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole
Nominal Thread Diameter:	0.875 Inches
Grip Length:	1.678 Inches Minimum And 1.698 Inches Maximum
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.590 Inches Minimum First Hole And 2.640 Inches Maximum First Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6714 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6714DU27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.