

**Description**

Fastener Length: 31/32", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | NAS673V10H                                |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-849-1581                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS673V10H Specifications

|                                              |                                                           |
|----------------------------------------------|-----------------------------------------------------------|
| <b>Thread Class:</b>                         | 3a                                                        |
| <b>Thread Direction:</b>                     | Right-hand                                                |
| <b>Thread Length:</b>                        | 0.313 Inches Minimum And 0.363 Inches Maximum             |
| <b>Fastener Length:</b>                      | 0.948 Inches Minimum And 0.978 Inches Maximum             |
| <b>Head Style:</b>                           | Hexagon                                                   |
| <b>Head Height:</b>                          | 0.110 Inches Minimum And 0.125 Inches Maximum             |
| <b>Width Between Flats:</b>                  | 0.367 Inches Minimum And 0.376 Inches Maximum             |
| <b>Hole Diameter:</b>                        | 0.046 Inches Minimum And 0.056 Inches Maximum             |
| <b>Grip Diameter:</b>                        | 0.1890 Inches Minimum And 0.1895 Inches Maximum           |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches                                              |
| <b>Grip Length:</b>                          | 0.615 Inches Minimum And 0.635 Inches Maximum             |
| <b>Hole Quantity:</b>                        | 3                                                         |
| <b>Hole Type:</b>                            | Drilled                                                   |
| <b>Thread Quantity Per Inch:</b>             | 32                                                        |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                             |
| <b>Hole Configuration Style:</b>             | Hexagon Corners                                           |
| <b>Surface Finish:</b>                       | 16.0 Microinches Threads                                  |
| <b>Surface Finish:</b>                       | 63.0 Microinches Bearing Surface Of Head                  |
| <b>Surface Finish:</b>                       | 63.0 Microinches Grip                                     |
| <b>Material:</b>                             | Titanium Alloy Uns R56400 Overall                         |
| <b>Material Document And Classification:</b> | Ams4967 Assn Std Single Material Response Overall         |
| <b>Thread Series Designator:</b>             | Unjf                                                      |
| <b>Specification/standard Data:</b>          | 80205-nas673 Professional/industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS673V10H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.