

Description

Fastener Length: 1-13/32", Thread: 10-32, Thread Length: 23/64", NAS673 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS673V17 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-836-8308 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



* See page 2 for technical characteristics

P/N NAS673V17 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.313 Inches Minimum And 0.363 Inches Maximum |
| Fastener Length: | 1.385 Inches Minimum And 1.415 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.110 Inches Nominal |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.052 Inches Minimum And 1.072 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Nas 621 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas673 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS673V17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.