

P/N NAS673V23H

Description

Fastener Length: 1-25/32", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6/3V23H
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-046-0565
Schodulo Pr	9109 00 2060

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



^{*} See page 2 for technical characteristics

P/N NAS673V23H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.363 Inches Maximum
Fastener Length:	1.761 Inches Minimum And 1.791 Inches Maximum
Head Style:	Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.428 Inches Minimum And 1.448 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Hexagon Corners
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Nas621 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas673 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS673V23H and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.