

Description

Fastener Length: 2-3/32", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS673V28H
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-044-3010
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS673V28H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.363 Inches Maximum
Fastener Length:	2.073 Inches Minimum And 2.103 Inches Maximum
Head Style:	Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Surface Finish:	16.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas673 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS673V28H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.