

**Description**

Fastener Length: 7/16", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS673V2D                            |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5306-00-927-7901                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS673V2D Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.338 Inches Minimum                              |
| <b>Fastener Length:</b>   | 0.463 Inches Nominal                              |
| <b>Head Style:</b>  | Hexagon   |
| <b>Head Height:</b>   | 0.110 Inches Nominal                              |
| <b>Width Between Flats:</b>   | 0.367 Inches Minimum And 0.376 Inches Maximum     |
| <b>Grip Diameter:</b>   | 0.1890 Inches Minimum And 0.1895 Inches Maximum   |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.070 Inches Nominal First Hole                   |
| <b>Nominal Thread Diameter:</b>   | 0.190 Inches                                      |
| <b>Grip Length:</b>   | 0.125 Inches Nominal                              |
| <b>Thread Quantity Per Inch:</b>  | 32  |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch                     |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 0.300 Inches Nominal First Hole                   |
| <b>Material:</b>  | Titanium Alloy Overall                            |
| <b>Material Document And Classification:</b>                            | Nas 621 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>  | Unf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS673V2D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.