

Description

Fastener Length: 3-13/16", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS673V56
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-501-4920
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS673V56 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	3.838 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.189 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	3.500 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Nas621 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS673V56> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.