

Description

Fastener Length: 3/4", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 5/16", drilled head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS673V7H
Minimum Qty (MOQ):	5
NSN:	5306-00-917-4607
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



P/N NAS673V7H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Minimum
Fastener Length:	0.776 Inches Nominal
Head Style:	Hexagon
Head Height:	0.110 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.438 Inches Nominal
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS673V7H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.