

Description

Fastener Length: 13/16", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS673V8 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5306-01-375-6024 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS673V8 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Nominal |
| Fastener Length: | 0.838 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.110 Inches Nominal |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.500 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Titanium Alloy Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS673V8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.