

Description

Fastener Length: 29/32", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS673V9D |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-117-4733 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N NAS673V9D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.313 Inches Minimum And 0.363 Inches Maximum |
| Fastener Length: | 0.885 Inches Minimum And 0.915 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.722 Inches Minimum First Hole And 0.752 Inches Maximum First Hole |
| Material: | Titanium Alloy Uns R54520 Overall |
| Material Document And Classification: | Nas621,comp 6al-4v Assn Std Single Material Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS673V9D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.