

**Description**

Fastener Length: 1-11/16", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS674V20H                           |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5306-00-431-7102                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS674V20H Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.400 Inches Minimum And 0.450 Inches Maximum                |
| <b>Fastener Length:</b>                      | 1.660 Inches Minimum And 1.690 Inches Maximum                |
| <b>Head Style:</b>                           | Hexagon  |
| <b>Head Height:</b>                          | 0.125 Inches Minimum And 0.140 Inches Maximum                |
| <b>Width Between Flats:</b>                  | 0.430 Inches Minimum And 0.439 Inches Maximum                |
| <b>Hole Diameter:</b>                        | 0.046 Inches Nominal   |
| <b>Grip Diameter:</b>                        | 0.2490 Inches Minimum And 0.2495 Inches Maximum              |
| <b>Nominal Thread Diameter:</b>              | 0.250 Inches   |
| <b>Grip Length:</b>                          | 1.240 Inches Minimum And 1.260 Inches Maximum                |
| <b>Hole Quantity:</b>                        | 3  |
| <b>Hole Type:</b>                            | Drilled  |
| <b>Thread Quantity Per Inch:</b>             | 28   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                                |
| <b>Hole Configuration Style:</b>             | Hexagon Corners  |
| <b>Material:</b>                             | Titanium Alloy Uns R54520 Overall                            |
| <b>Material Document And Classification:</b> | Nas621,comp 6al-4v Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf   |
| <b>Specification/standard Data:</b>          | 80205-nas674 Professional/industrial Association Standard    |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS674V20H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.