

## **P/N NAS674V21**

### **Description**

Fastener Length: 1-3/4", Thread: 1/4-28, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS674V21

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-899-2534

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS674V21 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	1.722 Inches Minimum And 1.752 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.302 Inches Minimum And 1.322 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Nas621,comp 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas674 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS674V21">https://military-fasteners.com/bolts/shear+bolts/NAS674V21</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.