

**Description**

Fastener Length: 2-9/16", Thread: 1/4-28, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS674V34                            |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5306-00-781-7639                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS674V34 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.400 Inches Minimum And 0.450 Inches Maximum             |
| <b>Fastener Length:</b>                      | 2.535 Inches Minimum And 2.565 Inches Maximum             |
| <b>Head Style:</b>                           | Hexagon   |
| <b>Head Height:</b>                          | 0.125 Inches Minimum And 0.140 Inches Maximum             |
| <b>Width Between Flats:</b>                  | 0.430 Inches Minimum And 0.439 Inches Maximum             |
| <b>Grip Diameter:</b>                        | 0.2490 Inches Minimum And 0.2495 Inches Maximum           |
| <b>Nominal Thread Diameter:</b>              | 0.250 Inches  |
| <b>Grip Length:</b>                          | 2.115 Inches Minimum And 2.135 Inches Maximum             |
| <b>Thread Quantity Per Inch:</b>             | 28  |
| <b>Surface Finish:</b>                       | 16.0 Microinches Threads                                  |
| <b>Surface Finish:</b>                       | 63.0 Microinches Bearing Surface Of Head                  |
| <b>Surface Finish:</b>                       | 63.0 Microinches Grip                                     |
| <b>Material:</b>                             | Titanium Alloy Uns R56400 Overall                         |
| <b>Material Document And Classification:</b> | Ams4967 Assn Std Single Material Response Overall         |
| <b>Thread Series Designator:</b>             | Unjf  |
| <b>Specification/standard Data:</b>          | 80205-nas674 Professional/industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS674V34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.