

Description

Fastener Length: 51/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS674V6D
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-927-7888
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS674V6D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Minimum
Fastener Length:	0.800 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.375 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.619 Inches Nominal First Hole
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS674V6D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.