

Description

Fastener Length: 59/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS674V8D |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5306-00-917-6203 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS674V8D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Minimum |
| Fastener Length: | 0.925 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Nominal |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.500 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.744 Inches Nominal First Hole |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Nas 621 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS674V8D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.