

Description

Fastener Length: 1-15/64", Thread: 1/4-24, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS675V12
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-879-0496
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS675V12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	1.204 Inches Minimum And 1.234 Inches Maximum
Head Style:	Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Surface Finish:	16.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Nas621,comp 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas675 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS675V12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.