

Description

Fastener Length: 2-11/64", Thread: 1/4-24, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS675V27
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-380-3629
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS675V27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.369 Inches Nominal
Fastener Length:	2.142 Inches Minimum And 2.172 Inches Maximum
Head Style:	Hexagon Extended Washer
Head Height:	0.171 Inches Minimum And 0.191 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.564 Inches Maximum
Extended Washer Diameter:	0.460 Inches Nominal
Extended Washer Thickness:	0.015 Inches Minimum And 0.025 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.678 Inches Minimum And 1.698 Inches Maximum
Thread Quantity Per Inch:	24
Material:	Titanium Alloy Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas675 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS675V27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.