

**Description**

Fastener Length: 2-11/64", Thread: 1/4-24, Thread Length: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS675V27
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-380-3629
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS675V27 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.369 Inches Nominal
<b>Fastener Length:</b>	2.142 Inches Minimum And 2.172 Inches Maximum
<b>Head Style:</b>	Hexagon Extended Washer
<b>Head Height:</b>	0.171 Inches Minimum And 0.191 Inches Maximum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.564 Inches Maximum
<b>Extended Washer Diameter:</b>	0.460 Inches Nominal
<b>Extended Washer Thickness:</b>	0.015 Inches Minimum And 0.025 Inches Maximum
<b>Grip Diameter:</b>	0.3115 Inches Minimum And 0.3120 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.678 Inches Minimum And 1.698 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Material:</b>	Titanium Alloy Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas675 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS675V27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.