

Description

Fastener Length: 3-7/64", Thread: 1/4-24, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS675V42 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-169-6766 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N NAS675V42 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.444 Inches Minimum And 0.494 Inches Maximum |
| Fastener Length: | 3.079 Inches Minimum And 3.109 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.156 Inches Minimum And 0.171 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Grip Diameter: | 0.3115 Inches Minimum And 0.3745 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 2.615 Inches Minimum And 2.635 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Surface Finish: | 16.0 Microinches Threads |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 63.0 Microinches Grip |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas675 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS675V42> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.