

Description

Fastener Length: 1-", Thread: 5/16-24, Thread Length: 15/32", NAS675 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS675V9
Minimum Qty (MOQ):	5
NSN:	5306-01-459-0819
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS675V9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Minimum
Fastener Length:	1.031 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	0.562 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas621 Assn Std Single Material Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas675 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS675V9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.