

**Description**

Fastener Length: 2-45/64", Thread: 3/8-24, Thread Length: 19/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS676V34                                 |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-131-2597                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS676V34 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.553 Inches Minimum And 0.603 Inches Maximum     |
| <b>Fastener Length:</b>                      | 2.688 Inches Minimum And 2.718 Inches Maximum     |
| <b>Head Style:</b>                           | Hexagon   |
| <b>Head Height:</b>                          | 0.188 Inches Minimum And 0.203 Inches Maximum     |
| <b>Width Between Flats:</b>                  | 0.553 Inches Minimum And 0.564 Inches Maximum     |
| <b>Grip Diameter:</b>                        | 0.3740 Inches Minimum And 0.3745 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>              | 0.375 Inches                                      |
| <b>Grip Length:</b>                          | 2.115 Inches Minimum And 2.135 Inches Maximum     |
| <b>Thread Quantity Per Inch:</b>             | 24  |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                     |
| <b>Material:</b>                             | Titanium Alloy Uns R56400 Overall                 |
| <b>Material Document And Classification:</b> | Ams4967 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS676V34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.