

Description

Fastener Length: 3-61/64", Thread: 1/4-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS676V54 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-469-5527 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS676V54 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.578 Inches Nominal |
| Fastener Length: | 3.938 Inches Minimum And 3.968 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.3740 Inches Minimum And 0.3745 Inches Maximum |
| End Item Identification: | C130p |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 3.375 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS676V54> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.