

**Description**

Fastener Length: 7/8", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS676V5H
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-917-6248
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS676V5H Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.578 Inches Minimum
<b>Fastener Length:</b>	0.890 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.188 Inches Nominal
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.564 Inches Maximum
<b>Hole Diameter:</b>	0.070 Inches Nominal
<b>Grip Diameter:</b>	0.3740 Inches Minimum And 0.3745 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.312 Inches Nominal
<b>Hole Quantity:</b>	3
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Hexagon Corners
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams4967 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS676V5H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.