

Description

Fastener Length: 7/8", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS676V5H
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-917-6248
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS676V5H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Minimum
Fastener Length:	0.890 Inches Nominal
Head Style:	Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.312 Inches Nominal
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS676V5H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.