

P/N NAS679A3W

Description

thread: 10-32, self-locking, low height hex nut, with internal wrenching, locknut, NAS679 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

BACN10JC3

SKU / Model: NAS679A3W

Minimum Qty (MOQ): 25

NSN: 5310-00-680-4892

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)













^{*} See page 2 for technical characteristics

P/N NAS679A3W Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Nut Style:	Hexagon
Nut Height:	0.188 Inches Maximum
End Item Identification:	B-1 Support Equipment; Aircraft;tf-33 Engine
Width Across Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Specification/standard Data:	26512-gn10u Manufacturers Standard

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/NAS679A3W and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+hexagon+nuts/NAS679A3W and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+hexagon+nuts/NAS679A3W and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+hexagon+nuts/NAS679A3W and selecting the properties of the properti