

Description

thread: 5/16-24, self locking, low height, without internal wrenching, NAS679 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[BACN10JC5](#)

| | |
|-------------------------|---|
| SKU / Model: | NAS679A5 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-807-1476 |
| Schedule B: | 7318.16.0030 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS679A5 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.520 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.251 Inches Minimum And 0.266 Inches Maximum |
| Nut Style: | Hexagon |
| Washer Thickness: | 0.023 Inches Minimum |
| Width Across Flats: | 0.367 Inches Minimum And 0.378 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 24 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.312 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/NAS679A5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.