

## **P/N NAS679C04MW**

## **Description**

Thread Size: 1/8", Nut Height: 1/8", Head Width: 1/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS679C04MW

Minimum Qty (MOQ): 10

NSN: 5310-00-803-4663

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS679C04MW Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Nut Style:	Hexagon
Nut Height:	0.125 Inches Maximum
Width Across Flats:	0.240 Inches Minimum And 0.252 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Special Features:	Internal Wrenching
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Specification/standard Data:	80205-nas679 Professional/industrial Association Standard

### **How to Order**

Order this locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS679C04MW">https://military-fasteners.com/nuts/locknuts/NAS679C04MW</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.