

**Description**

Thread Size: 1/8", Nut Height: 1/8", Head Width: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS679C06W                                |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5310-00-680-9304                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS679C06W Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3b  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Locking Feature:</b>                               | Prevailing Torque All Metal Design                        |
| <b>Nut Style:</b>                                     | Hexagon   |
| <b>Nut Height:</b>                                    | 0.141 Inches Maximum                                      |
| <b>Width Across Flats:</b>                            | 0.302 Inches Minimum And 0.314 Inches Maximum             |
| <b>Temp Rating:</b>                                   | 800.0 Deg Fahrenheit Nominal                              |
| <b>Thread Series:</b>                                 | Unjc  |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Nominal Thread Size:</b>                           | 0.138 Inches  |
| <b>Countersink Angle:</b>                             | 120.0 Degrees Nominal Nut                                 |
| <b>Bearing Surface Type:</b>                          | Chamfered Or Washer Faced                                 |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches   |
| <b>Special Features:</b>                              | Interanl Wrenching  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall                                    |
| <b>Material Document And Classification:</b>          | Ams 5525 Assn Std Single Material Response Overall        |
| <b>Precious Material:</b>                             | Silver  |
| <b>Surface Treatment:</b>                             | Silver Overall  |
| <b>Surface Treatment Document And Classification:</b> | Ams 2410 Assn Std Single Treatment Response Overall       |
| <b>Specification/standard Data:</b>                   | 80205-nas679 Professional/industrial Association Standard |

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS679C06W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.