

Description

thread: 8-32, self-locking low height hex nut, corrosion resistant steel, with internal wrenching

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[NAS679-C08W](#)

| | |
|-------------------------|---|
| SKU / Model: | NAS679C08W |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-00-680-9305 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS679C08W Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Nut Style: | Hexagon |
| Nut Height: | 0.188 Inches Maximum |
| Width Across Flats: | 0.334 Inches Minimum And 0.346 Inches Maximum |
| Temp Rating: | 800.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Countersink Angle: | 120.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Special Features: | Internal Wrenching |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Overall |
| Precious Material: | Silver |
| Surface Treatment: | Silver Overall |
| Surface Treatment Document And Classification: | Ams 2410 Assn Std Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas679 Professional/industrial Association Standard |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/NAS679C08W and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.