

**Description**

Thread: 1/4-28, Thread Size: 1/4", Nut Height: 7/32", Head Width: 27/64", NAS679 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS679C4M                                 |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5310-00-813-3232                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS679C4M Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3b  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Locking Feature:</b>                               | Prevailing Torque All Metal Design                  |
| <b>Lubrication:</b>                                   | Dry Film Lubricant                                  |
| <b>Nut Style:</b>                                     | Hexagon   |
| <b>Nut Height:</b>                                    | 0.219 Inches Maximum                                |
| <b>Width Across Flats:</b>                            | 0.430 Inches Minimum And 0.439 Inches Maximum       |
| <b>Temp Rating:</b>                                   | 450.0 Deg Fahrenheit Nominal                        |
| <b>Thread Series:</b>                                 | Unjf  |
| <b>Thread Quantity Per Inch:</b>                      | 28  |
| <b>Nominal Thread Size:</b>                           | 0.250 Inches  |
| <b>Countersink Angle:</b>                             | 120.0 Degrees Nominal Nut                           |
| <b>Bearing Surface Type:</b>                          | Chamfered Or Washer Faced                           |
| <b>Material:</b>                                      | Iron Alloy 660 Overall                              |
| <b>Material Document And Classification:</b>          | Ams 5525 Assn Std Single Material Response Overall  |
| <b>Precious Material:</b>                             | Silver  |
| <b>Surface Treatment:</b>                             | Silver Overall                                      |
| <b>Surface Treatment Document And Classification:</b> | Ams 2410 Assn Std Single Treatment Response Overall |

## How to Order

Order this self-locking hexagon nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+hexagon+nuts/NAS679C4M](https://military-fasteners.com/nuts/self_locking+hexagon+nuts/NAS679C4M) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.