

## **P/N NAS679C6**

### **Description**

Thread Size: 3/4", Nut Height: 9/32", Head Width: 35/64", NAS679 series nut

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

#### **Additional Information**

SKU / Model:	NAS679C6
Minimum Qty (MOQ):	5
NSN:	5310-00-680-9297
Schedule B:	7318.16.0085
FCCN:	FAR99



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS679C6 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Nut Height:	0.282 Inches Nominal
Width Across Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Uns
Thread Quantity Per Inch:	24
Hardness Rating:	Not Rated
Nominal Thread Size:	0.750 Inches
Bearing Surface Type:	Any Acceptable
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Specification/standard Data:	80205-nas679c6 Professional/industrial Association Standard

## **How to Order**

Order this locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS679C6">https://military-fasteners.com/nuts/locknuts/NAS679C6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.