

## P/N NAS6803A23

### **Description**

Fastener Length: 1-51/64", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS6803A23

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-411-8672

Schedule B: 8108.90.3060

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS6803A23 Specifications**

| Thread Class:                                  | 3a   |
|--|--|
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.345 Inches Nominal   |
| Fastener Length:                               | 1.768 Inches Minimum And 1.798 Inches Maximum  |
| Head Style:                                    | Dished Hexagon   |
| Head Height:                                   | 0.110 Inches Minimum And 0.125 Inches Maximum  |
| Width Between Flats:                           | 0.367 Inches Minimum And 0.376 Inches Maximum  |
| Grip Diameter:                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum  |
| Nominal Thread Diameter:                       | 0.190 Inches   |
| Grip Length:                                   | 1.428 Inches Minimum And 1.448 Inches Maximum  |
| Thread Quantity Per Inch:                      | 32   |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch  |
| Material:                                      | Titanium Alloy Uns R56400 Overall  |
| Material Document And Classification:          | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment:                             | Aluminum Overall   |
| Surface Treatment Document And Classification: | Nas 4006 Assn Std Single Treatment Response Overall  |
| Thread Series Designator:                      | Unjf   |
| Specification/standard Data:                   | 80205-nas6803 Professional/industrial Association Standard   |

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6803A23">https://military-fasteners.com/bolts/shear+bolts/NAS6803A23</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6803A23">https://military-fasteners.com/bolts/shear+bolts/NAS6803A23</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6803A23">https://military-fasteners.com/bolts/shear+bolts/NAS6803A23</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6803A23">https://military-fasteners.com/bolts/shear+bolts/NAS6803A23</a> and selecting the quantity you want then click "add to cart".