

Description

Fastener Length: 19/32", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6803HU4
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-364-3564
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS6803HU4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.585 Inches Minimum And 0.605 Inches Maximum
Head Style:	Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall And Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6803 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6803HU4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.