

**Description**

Fastener Length: 1-7/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS6803U12X                          |
| Minimum Qty (MOQ):      | 1 EA                                 |
| NSN:                    | 5306-01-208-3850                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS6803U12X Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.320 Inches Minimum And 0.370 Inches Maximum  |
| <b>Fastener Length:</b>                      | 1.080 Inches Minimum And 1.110 Inches Maximum  |
| <b>Head Style:</b>                           | Dished Hexagon   |
| <b>Head Height:</b>                          | 0.110 Inches Minimum And 0.125 Inches Maximum  |
| <b>Width Between Flats:</b>                  | 0.367 Inches Minimum And 0.376 Inches Maximum  |
| <b>Shoulder Diameter:</b>                    | 0.2021 Inches Minimum And 0.2026 Inches Maximum First Shoulder   |
| <b>Shoulder Length:</b>                      | 0.740 Inches Minimum And 0.760 Inches Maximum First Shoulder   |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch  |
| <b>Shoulder Shape:</b>                       | Round First Shoulder   |
| <b>Material:</b>                             | Titanium Alloy Overall   |
| <b>Material Document And Classification:</b> | Ams4928 Assn Std Single Material Response Or Ams4967,comp 6al-4v Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf   |
| <b>Specification/standard Data:</b>          | 80205-nas6803 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6803U12X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.