

**Description**

Fastener Length: 2-39/64", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS6803U36       |
| Minimum Qty (MOQ): | 1 EA             |
| NSN:               | 5306-01-456-0416 |
| Schedule B:        | 8108.90.3060     |
| ECCN:              | 9A991            |

NO IMAGE  
AVAILABLE

## P/N NAS6803U36 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.345 Inches Nominal  |
| <b>Fastener Length:</b>                      | 2.580 Inches Minimum And 2.610 Inches Maximum   |
| <b>Head Style:</b>                           | Hexagon   |
| <b>Head Height:</b>                          | 0.110 Inches Minimum And 0.125 Inches Maximum   |
| <b>Width Between Flats:</b>                  | 0.367 Inches Minimum And 0.376 Inches Maximum   |
| <b>Grip Diameter:</b>                        | 0.1890 Inches Minimum And 0.1895 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches  |
| <b>Grip Length:</b>                          | 2.240 Inches Minimum And 2.260 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>             | 32  |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head  |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads  |
| <b>Material:</b>                             | Titanium Alloy Uns R56400 Overall   |
| <b>Material Document And Classification:</b> | Ams4928 Assn Std Single Material Response Overall And Ams4967 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf  |
| <b>Specification/standard Data:</b>          | 80205-nas6803 Professional/industrial Association Standard  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6803U36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.