

**Description**

Fastener Length: 43/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6803U5Y
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-207-9312
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

## P/N NAS6803U5Y Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.320 Inches Minimum And 0.370 Inches Maximum
<b>Fastener Length:</b>	0.642 Inches Minimum And 0.672 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.110 Inches Minimum And 0.125 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Shoulder Diameter:</b>	0.2177 Inches Minimum And 0.2182 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum First Shoulder
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams4928 Assn Std Single Material Response Or Ams4967,comp 6al-4v Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6803 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6803U5Y> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.