

**Description**

Fastener Length: 2-19/64", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6804U30
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-488-2318
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS6804U30 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Nominal
<b>Fastener Length:</b>	2.300 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.429 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.249 Inches Nominal
<b>End Item Identification:</b>	F-22 Raptor
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.875 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Bolt,hex Head,close Tolerance,6al-4v Titanium Alloy,long Thread,nonlocking
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6804U30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.