

Description

Fastener Length: 1-1/32", Thread: 1/4-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6805U9
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-352-3120
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6805U9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	1.016 Inches Minimum And 1.046 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6805 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6805U9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.