



Military-Fasteners.com

**P/N NAS6806U12**

## Description

Fastener Length: 1-5/16", Thread: 3/8-24, Thread Length: 9/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS6806U12
Minimum Qty (MOQ):	1
NSN:	5306-01-532-8923
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6806U12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.578 Inches Nominal
<b>Fastener Length:</b>	1.328 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.188 Inches Minimum And 0.203 Inches Maximum
<b>Width Between Flats:</b>	0.554 Inches Minimum And 0.564 Inches Maximum
<b>Grip Diameter:</b>	0.3740 Inches Minimum And 0.3745 Inches Maximum
<b>End Item Identification:</b>	C-130 Amp Cmb
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.750 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Bolt,shoulder
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams4967 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6806 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6806U12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.