

Description

Fastener Length: 1-11/16", Thread: 3/8-24, Thread Length: 9/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6806U18
Minimum Qty (MOQ):	1
NSN:	5306-01-529-5418
Schedule B:	8108.90.3060
ECCN:	EAR99



P/N NAS6806U18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	1.703 Inches Nominal
Head Style:	Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
End Item Identification:	F-22
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.125 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt,hex Head,close Tolerance,6al-4v Titanium Alloy,long Thread
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6806U18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.