

Description

Fastener Length: 2-5/64", Thread: 3/8-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6806U24
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-456-0516
Schedule B:	8108.90.3060
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS6806U24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	2.063 Inches Minimum And 2.093 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.490 Inches Minimum And 1.510 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6806 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6806U24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.