

**Description**

Thread Size: 1/8", Nut Length: 15/16", Nut Height: 5/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS680A06        |
| Minimum Qty (MOQ): | 45 EA            |
| NSN:               | 5310-00-726-2494 |
| Schedule B:        | 7318.16.0030     |
| ECCN:              | 9A991.           |



\* See page 2 for technical characteristics

## P/N NAS680A06 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3b  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Locking Feature:</b>   | Prevailing Torque All Metal Design                        |
| <b>Lubrication:</b>   | Dry Film Lubricant  |
| <b>Mounting Hole Diameter:</b>  | 0.098 Inches Minimum And 0.103 Inches Maximum             |
| <b>Nut Style:</b>   | Plate   |
| <b>Nut Length:</b>  | 0.948 Inches Maximum                                      |
| <b>Nut Height:</b>  | 0.171 Inches Maximum                                      |
| <b>Plate Thickness:</b>   | 0.047 Inches Maximum                                      |
| <b>Plate Width:</b>   | 0.265 Inches Maximum                                      |
| <b>Nut Mounting Provision:</b>  | Straight Holes  |
| <b>Mounting Hole Arrangement Style:</b>                               | 2 Holes   |
| <b>Distance From Aperture Center To Mounting Hole Center:</b>         | 0.344 Inches Nominal                                      |
| <b>Center To Center Distance Between Mounting Holes Along Length:</b> | 0.686 Inches Minimum And 0.690 Inches Maximum             |
| <b>Temp Rating:</b>   | 450.0 Deg Fahrenheit Nominal                              |
| <b>Thread Series:</b>   | Unjc  |
| <b>Thread Quantity Per Inch:</b>                                      | 32  |
| <b>Nominal Thread Size:</b>   | 0.138 Inches  |
| <b>Material:</b>  | Steel Overall   |
| <b>Surface Treatment:</b>   | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b>                 | Qq-p-416 Fed Spec Single Treatment Response Overall       |
| <b>Specification/standard Data:</b>                                   | 80205-nas680 Professional/industrial Association Standard |

## How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS680A06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.