

Description

Thread Size: 1/8", Nut Length: 15/16", Nut Height: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS680A06K |
| Minimum Qty (MOQ): | 35 EA |
| NSN: | 5310-01-492-8405 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS680A06K Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Nut Style: | Plate |
| Nut Length: | 0.948 Inches Nominal |
| Nut Height: | 0.171 Inches Nominal |
| Plate Thickness: | 0.047 Inches Nominal |
| Plate Width: | 0.265 Inches Nominal |
| Nut Mounting Provision: | Straight Holes |
| Mounting Provision Location: | Opposite Nut Projection Side |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.138 Inches |
| Mounting Hole Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type II, Class 2 Fed Spec 1st Treatment Response Overall |

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS680A06K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.